


WTT2 TORCHES


Simple and reliable, this range is adapted to the most common applications.



Extra-flexible, high-performance cable.



Easy pivoting handle (for EB handles).




Standardized wear parts.



Handle – made with high temperature silicon rubber.


MODEL		AIR COOLING							
		WTT2 9		WTT2 17		WTT2 26			
Duty cycle at 40 °C	60%	80 A		100 A		130 A			
	35%	110 A		135 A		180 A			
Original equipment	back cap	Long							
	nozzle	Ø 9,6 mm		Ø 9,6 mm		Ø 12,8 mm			
	electrode	Ø 1,6 mm		Ø 2,0 mm		Ø 2,4 mm			
Length		4 m	8 m	4 m	8 m	4 m	8 m		
Handle	RL	Connection	S	P000022591	P000244238	P000244198	P000244230	P000244212	P000244222
			C5B	P000022592	P000244236	P000244196	P000244228	P000244210	P000244220
	EB	S	P000022590	P000244242	P000244194	P000244234	P000244208	P000244226	
		C5B	P000022588	–	P000244192	P000244232	P000244206	P000244224	
	V	V (Conn. 9 mm)	P000022589	–	P000244200	–	–	–	
		V (Conn. 13 mm)	–	–	P000028668	–	P000244214	–	
EB-FLEX	S / C5B		P000027721	–	P000027722	P000027723	P000027724	P000027725	

Connections



Connector :

Shaped cable output for improved robustness.



MODEL		WATER COOLING					
		WTT2 20 W		WTT2 18 W			
Duty cycle at 40 °C	100%	200 A		320 A			
	60%	250 A		350 A			
Original equipment	back cap	Long					
	nozzle	Ø 12,8 mm		Ø 16 mm			
	electrode	Ø 2,4 mm		Ø 3,2 mm			
Length		4 m	8 m	4 m	8 m		
Handl	EB	Connection	S	P000022593	P000022604	P000022597	P000022600
			C5B	P000022594	P000022603	P000022598	P000022599
	EB-FLEX	S	P000244204	P000022606	P000022595	P000022602	
		C5B	P000244202	P000022605	P000022596	P000022601	
	S/C5B	P000027726	P000027727	P000027728	P000027729		


Handle



RL



EB



V



EB-FLEX